FY H. Lithium Bearing Grease





Lithium Bearing Grease

so arings.com

Made in U.S.A.

FYH Lithium Bearing Grease is an NLGI 2 lithium complex grease that provides substantial improvements over general purpose lithium soap based lubricants. It functions extremely well under a variety of highly demanding operating conditions including wide temperature ranges, variable speeds, water contamination, vibration, heavy loads, and shock loads. In addition to its high quality base oils, it contains oxidation inhibitors and extreme pressure additives which are both crucial to maintaining a high degree of protection where high loading and moisture and chemicals are present.

FYH Lithium Bearing Grease exhibits excellent water wash-out resistance, and extensive testing has proven this lubricant to be successful where such challenging conditions exist. Due to its compatibility with the existing formula, not only can the new and improved formulation enhance operating characteristics, it can also extend the useful life of units that are currently in operation.

Technical data

| NLGI Grade | |
|---|--|
| Soap Type Lithium Complex | |
| Color Green | |
| Appearance Smooth | |
| Penetration, ASTM D 217 Worked 60 Strokes | |
| Roll Stability, ASTM D 1831, % Change | |
| Dropping Point, ASTM D 2265, °F Min 500 | |
| Oxidation Stability, ASTM D 942, psi Loss | |

| Water Washout, ASTM D 1264, % Loss @ 175°F |
|--|
| Grease Mobility, USS, g/Min. 6.88 (150 psi, 0°F, #1 Orifice) |
| Four Ball Wear, ASTM D 2266, mm Scar Dia. Max 0.60 |
| Four Ball EP Weld Point, ASTM D 2596, Min |
| Timken EP Test, ASTM D 2509, OK load lbs 50 |
| Mineral Oil, ASTM D 445 60 - 80 Viscosity at 210°F, SUS 700 - 900 |
| Rust Test, ASTM D 1743, 100 Hrs., 100°F Pass |
| Operating Temparature Range $-4^{\circ}F$ - $320^{\circ}F$ (- $20^{\circ}C$ - $160^{\circ}C$) |

SHIPPING-AVAILABILITY

FYH Lithium Bearing Grease is available in 14 oz. cartridges, 35 pound pails, 120 pound kegs, 400 pound drums.

FYH BEARING UNITS USA, INC.

13201 FYH Drive Huntley, Illinois 60142

TEL: 847-487-9111 FAX: 847-487-9222 E-mail: sales@fyhusa.com

